TECHNICAL DATA

DOUBLEFLEX

OLYMPIA III

Building height: 83 mm Board: 2200 x 139 x 21.0 mm Format: 2-strip €€







FLOOR HEATING ADDITIONAL COLOUR




UNEVEN SUB-FLOOR



VARIABLE HEIGHTS






PERFORMANCE ACCORDING TO EN14904		SHOCK ABSORPTION		DEFORMATION		FRICTION	BALL BOUNCE	ROLLING LOAD
		TYPE 3: ≥ 40% ≤ 55%	TYPE 4 : ≥ 55% ≤ 75%	TYPE 3: ≥ 1.8mm ≤ 3.5mm	TYPE 4: ≥ 2.3mm ≤ 5.0mm	80 - 110	≥ 90%	Min. 1500N
Doubleflex	OLYMPIA III		58%		2.6 mm	-	95%	OK







Tongue & groove

Package overview Package overview Pack size: 6 boards = 1.83 m² (21 kg) Pallet size: 42 packs = 76.86 m² (882 kg) We reserve the right to deliver one element as random length in each pack. Maple Can. Sport *

Doubleflex Olympia III Construction Details (from the top to the edge of concrete/subfloor)					
Doubleflex Olympia III 2200 x 139 x 21.0 mm EN 14904		21 mm			
Double swing beam Pre-fabricated in fixed-length, screwed, with intermediate webs and supporting cushion pads. Laid out in longitudinal direction of the hall. Centre to centre 500 mm		46 mm			
Counter floor In fixed-length, nailed crosswise into the double swing beams Centre to centre approx. 137 mm		16 mm			
 Hardwood toplayer BOEN Sport parquet With solid wood top layer 6 mm thick, tongue and groove nailed into the counter floor. 6 times pre-factory sealed and UV-hardend with "protect Ultra sealing", which is free of formaldehyde and solvents. 		21 mm			
PE Plastic sheet Laid out loosely, approx. 100 mm overlapped at the joints		0.05 mm			
Construction height (without top layer)		83 mm			

All planks are made of nordic spruce wood (dimensions: 97/16 mm), and are parallel edged, kiln-dried, planed all-over and fabricated in fixed-length.

* FSC™ Mix 70%

MAINTENANCE

We recommend starting a regular system of maintenance from day one. The amount of maintenance your floor requires will depend on how you use and treat it. For more information: boensport.com

The environment is at the core of all we do

BOEN hardwood flooring is a product of nature. As a procurer of timber BOEN has an important heritage to maintain. Constant involvement in resource preservation methods, participation in reforestation programmes and the development of alternatives to exotic species shows Boen's dedication towards the environment. All timber purchased by BOEN is supplied from sources who belong to one or more forestry schemes or are working towards certification. BOEN Bruk (Norway) FSC™ C051117, BOEN Parkett Deutschland (Germany) FSC™ C101713, BOEN Lietuva (Lithuania) FSC™ C021510, BOEN UK FSC™ C047288, BOEN US FSC™ C095158. www.fsc.org, FSC – The mark of responsible forestry.











